

a) suppliers name or trade mark		2VV s.r.o.														
b)		c)	d)	f)	g)	h)	i)	j)	k)	l)	n)	o)		p)	q)	r)
supplier's model identifier	ErP - Conformity (2016/2018/2020)	ErP - Typology (RVU or NRVU)	ErP - Multi-speed drive or variable speed drive	ErP - Thermal efficiency (%)	ErP - nominal air flow (m3/s)	ErP - Effective electric power (kW)	ErP - SFPInt (W/(m3/s))	ErP - face velocity at the nominal airflow (m/s)	ErP - nominal external pressure (Pa)	ErP - Internal pressure drop of the components (Pa)	ErP -Static efficiency of fans (%)	ErP - maximum external leakage (%)	ErP - maximum internal leakage (%)	ErP - Energy classification of the filters	ErP - Description of the visual filter warning for the NRVU with filters	ErP - Casing sound power level (LwA(dB))
HR953-150U CBE75-XS0	2018	NRVU	VSD	83,3	0,417	0,85	955	1,38	250	245	56,9	2,2	2,7	E	control panel (HMI)	54,8
HR953-150U CBE75-XE1	2018	NRVU	VSD	83,3	0,417	0,85	955	1,38	250	245	56,9	2,2	2,7	E	control panel (HMI)	54,8
HR953-150U CBE75-XV1	2018	NRVU	VSD	83,3	0,417	0,85	955	1,38	250	245	56,9	2,2	2,7	E	control panel (HMI)	54,8
HR953-150U CBE75-XVC	2018	NRVU	VSD	83,3	0,417	0,85	955	1,38	250	245	56,9	2,2	2,7	E	control panel (HMI)	54,8
HR953-150U CBE75-XD3	2018	NRVU	VSD	83,3	0,417	0,85	955	1,38	250	245	56,9	2,2	2,7	E	control panel (HMI)	54,8
HR953-150U CBE75-ES0	2018	NRVU	VSD	83,3	0,417	0,85	955	1,38	250	245	56,9	2,2	2,7	E	control panel (HMI)	54,8
HR953-150U CBE75-EE1	2018	NRVU	VSD	83,3	0,417	0,85	955	1,38	250	245	56,9	2,2	2,7	E	control panel (HMI)	54,8
HR953-150U CBE75-EV1	2018	NRVU	VSD	83,3	0,417	0,85	955	1,38	250	245	56,9	2,2	2,7	E	control panel (HMI)	54,8
HR953-150U CBE75-EVC	2018	NRVU	VSD	83,3	0,417	0,85	955	1,38	250	245	56,9	2,2	2,7	E	control panel (HMI)	54,8
HR953-150U CBE75-ED3	2018	NRVU	VSD	83,3	0,417	0,85	955	1,38	250	245	56,9	2,2	2,7	E	control panel (HMI)	54,8
HR953-220U CBE75-XS0	2018	NRVU	VSD	83,9	0,611	1,08	731	1,35	270	217	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U CBE75-XE1	2018	NRVU	VSD	83,9	0,611	1,08	731	1,35	270	217	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U CBE75-XV1	2018	NRVU	VSD	83,9	0,611	1,08	731	1,35	270	217	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U CBE75-XVC	2018	NRVU	VSD	83,9	0,611	1,08	731	1,35	270	217	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U CBE75-XD3	2018	NRVU	VSD	83,9	0,611	1,08	731	1,35	270	217	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U CBE75-ES0	2018	NRVU	VSD	83,9	0,611	1,08	731	1,35	270	217	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U CBE75-EE1	2018	NRVU	VSD	83,9	0,611	1,08	731	1,35	270	217	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U CBE75-EV1	2018	NRVU	VSD	83,9	0,611	1,08	731	1,35	270	217	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U CBE75-EVC	2018	NRVU	VSD	83,9	0,611	1,08	731	1,35	270	217	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U CBE75-ED3	2018	NRVU	VSD	83,9	0,611	1,08	731	1,35	270	217	66,4	1,6	1,6	E	control panel (HMI)	54,4
s) internet address	https://www.2vv.cz/en/products/															

a) suppliers name or trade mark		2VV s.r.o.														
b)		c)	d)	f)	g)	h)	i)	j)	k)	l)	n)	o)		p)	q)	r)
supplier's model identifier	ErP - Conformity (2016/2018/2020)	ErP - Typology (RVU or NRVU)	ErP - Multi-speed drive or variable speed drive	ErP - Thermal efficiency (%)	ErP - nominal air flow (m3/s)	ErP - Effective electric power (kW)	ErP - SFPint (W/(m3/s))	ErP - face velocity at the nominal airflow (m/s)	ErP - nominal external pressure (Pa)	ErP - Internal pressure drop of the components (Pa)	ErP -Static efficiency of fans (%)	ErP - maximum external leakage (%)	ErP - maximum internal leakage (%)	ErP - Energy classification of the filters	ErP - Description of the visual filter warning for the NRVU with filters	ErP - Casing sound power level (LwA(dB))
HR953-320U CBE75-XS0	2018	NRVU	VSD	81,4	0,889	1,51	695	1,48	300	234	68,5	1,3	1,8	E	control panel (HMI)	56,3
HR953-320U CBE75-XE1	2018	NRVU	VSD	81,4	0,889	1,51	695	1,48	300	234	68,5	1,3	1,8	E	control panel (HMI)	56,3
HR953-320U CBE75-XV1	2018	NRVU	VSD	81,4	0,889	1,51	695	1,48	300	234	68,5	1,3	1,8	E	control panel (HMI)	56,3
HR953-320U CBE75-XVC	2018	NRVU	VSD	81,4	0,889	1,51	695	1,48	300	234	68,5	1,3	1,8	E	control panel (HMI)	56,3
HR953-320U CBE75-XD3	2018	NRVU	VSD	81,4	0,889	1,51	695	1,48	300	234	68,5	1,3	1,8	E	control panel (HMI)	56,3
HR953-320U CBE75-ES0	2018	NRVU	VSD	81,4	0,889	1,51	695	1,48	300	234	68,5	1,3	1,8	E	control panel (HMI)	56,3
HR953-320U CBE75-EE1	2018	NRVU	VSD	81,4	0,889	1,51	695	1,48	300	234	68,5	1,3	1,8	E	control panel (HMI)	56,3
HR953-320U CBE75-EV1	2018	NRVU	VSD	81,4	0,889	1,51	695	1,48	300	234	68,5	1,3	1,8	E	control panel (HMI)	56,3
HR953-320U CBE75-EVC	2018	NRVU	VSD	81,4	0,889	1,51	695	1,48	300	234	68,5	1,3	1,8	E	control panel (HMI)	56,3
HR953-320U CBE75-ED3	2018	NRVU	VSD	81,4	0,889	1,51	695	1,48	300	234	68,5	1,3	1,8	E	control panel (HMI)	56,3
HR953-470U CBE75-XS0	2018	NRVU	VSD	82,5	1,306	2,54	894	1,43	320	296	68,5	0,9	2,3	E	control panel (HMI)	61,1
HR953-470U CBE75-XE1	2018	NRVU	VSD	82,5	1,306	2,54	894	1,43	320	296	68,5	0,9	2,3	E	control panel (HMI)	61,1
HR953-470U CBE75-XV1	2018	NRVU	VSD	82,5	1,306	2,54	894	1,43	320	296	68,5	0,9	2,3	E	control panel (HMI)	61,1
HR953-470U CBE75-XVC	2018	NRVU	VSD	82,5	1,306	2,54	894	1,43	320	296	68,5	0,9	2,3	E	control panel (HMI)	61,1
HR953-470U CBE75-XD3	2018	NRVU	VSD	82,5	1,306	2,54	894	1,43	320	296	68,5	0,9	2,3	E	control panel (HMI)	61,1
HR953-470U CBE75-ES0	2018	NRVU	VSD	82,5	1,306	2,54	894	1,43	320	296	68,5	0,9	2,3	E	control panel (HMI)	61,1
HR953-470U CBE75-EE1	2018	NRVU	VSD	82,5	1,306	2,54	894	1,43	320	296	68,5	0,9	2,3	E	control panel (HMI)	61,1
HR953-470U CBE75-EV1	2018	NRVU	VSD	82,5	1,306	2,54	894	1,43	320	296	68,5	0,9	2,3	E	control panel (HMI)	61,1
HR953-470U CBE75-EVC	2018	NRVU	VSD	82,5	1,306	2,54	894	1,43	320	296	68,5	0,9	2,3	E	control panel (HMI)	61,1
HR953-470U CBE75-ED3	2018	NRVU	VSD	82,5	1,306	2,54	894	1,43	320	296	68,5	0,9	2,3	E	control panel (HMI)	61,1
s) internet address	https://www.2vv.cz/en/products/															

a) suppliers name or trade mark		2VV s.r.o.														
b)		c)	d)	f)	g)	h)	i)	j)	k)	l)	n)	o)		p)	q)	r)
supplier's model identifier	ErP - Conformity (2016/2018/2020)	ErP - Typology (RVU or NRVU)	ErP - Multi-speed drive or variable speed drive	ErP - Thermal efficiency (%)	ErP - nominal air flow (m3/s)	ErP - Effective electric power (kW)	ErP - SFPint (W/(m3/s))	ErP - face velocity at the nominal airflow (m/s)	ErP - nominal external pressure (Pa)	ErP - Internal pressure drop of the components (Pa)	ErP -Static efficiency of fans (%)	ErP - maximum external leakage (%)	ErP - maximum internal leakage (%)	ErP - Energy classification of the filters	ErP - Description of the visual filter warning for the NRVU with filters	ErP - Casing sound power level (LwA(dB))
HR953-150U EBE75-XS0	2018	NRVU	VSD	74,4	0,417	0,75	684	1,38	250	181	56,9	2,2	2,7	E	control panel (HMI)	53,8
HR953-150U EBE75-XE1	2018	NRVU	VSD	74,4	0,417	0,75	684	1,38	250	181	56,9	2,2	2,7	E	control panel (HMI)	53,8
HR953-150U EBE75-XV1	2018	NRVU	VSD	74,4	0,417	0,75	684	1,38	250	181	56,9	2,2	2,7	E	control panel (HMI)	53,8
HR953-150U EBE75-XVC	2018	NRVU	VSD	74,4	0,417	0,75	684	1,38	250	181	56,9	2,2	2,7	E	control panel (HMI)	53,8
HR953-150U EBE75-XD3	2018	NRVU	VSD	74,4	0,417	0,75	684	1,38	250	181	56,9	2,2	2,7	E	control panel (HMI)	53,8
HR953-150U EBE75-ES0	2018	NRVU	VSD	74,4	0,417	0,75	684	1,38	250	181	56,9	2,2	2,7	E	control panel (HMI)	53,8
HR953-150U EBE75-EE1	2018	NRVU	VSD	74,4	0,417	0,75	684	1,38	250	181	56,9	2,2	2,7	E	control panel (HMI)	53,8
HR953-150U EBE75-EV1	2018	NRVU	VSD	74,4	0,417	0,75	684	1,38	250	181	56,9	2,2	2,7	E	control panel (HMI)	53,8
HR953-150U EBE75-EVC	2018	NRVU	VSD	74,4	0,417	0,75	684	1,38	250	181	56,9	2,2	2,7	E	control panel (HMI)	53,8
HR953-150U EBE75-ED3	2018	NRVU	VSD	74,4	0,417	0,75	684	1,38	250	181	56,9	2,2	2,7	E	control panel (HMI)	53,8
HR953-220U EBE75-XS0	2018	NRVU	VSD	79,1	0,611	1,02	622	1,35	270	187	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U EBE75-XE1	2018	NRVU	VSD	79,1	0,611	1,02	622	1,35	270	187	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U EBE75-XV1	2018	NRVU	VSD	79,1	0,611	1,02	622	1,35	270	187	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U EBE75-XVC	2018	NRVU	VSD	79,1	0,611	1,02	622	1,35	270	187	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U EBE75-XD3	2018	NRVU	VSD	79,1	0,611	1,02	622	1,35	270	187	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U EBE75-ES0	2018	NRVU	VSD	79,1	0,611	1,02	622	1,35	270	187	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U EBE75-EE1	2018	NRVU	VSD	79,1	0,611	1,02	622	1,35	270	187	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U EBE75-EV1	2018	NRVU	VSD	79,1	0,611	1,02	622	1,35	270	187	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U EBE75-EVC	2018	NRVU	VSD	79,1	0,611	1,02	622	1,35	270	187	66,4	1,6	1,6	E	control panel (HMI)	54,4
HR953-220U EBE75-ED3	2018	NRVU	VSD	79,1	0,611	1,02	622	1,35	270	187	66,4	1,6	1,6	E	control panel (HMI)	54,4
s) internet address	https://www.2vv.cz/en/products/															

a) suppliers name or trade mark		2VV s.r.o.														
b)		c)	d)	f)	g)	h)	i)	j)	k)	l)	n)	o)		p)	q)	r)
supplier's model identifier	ErP - Conformity (2016/2018/2020)	ErP - Typology (RVU or NRVU)	ErP - Multi-speed drive or variable speed drive	ErP - Thermal efficiency (%)	ErP - nominal air flow (m3/s)	ErP - Effective electric power (kW)	ErP - SFPint (W/(m3/s))	ErP - face velocity at the nominal airflow (m/s)	ErP - nominal external pressure (Pa)	ErP - Internal pressure drop of the components (Pa)	ErP - Static efficiency of fans (%)	ErP - maximum external leakage (%)	ErP - maximum internal leakage (%)	ErP - Energy classification of the filters	ErP - Description of the visual filter warning for the NRVU with filters	ErP - Casing sound power level (LwA(dB))
HR953-320U EBE75-XS0	2018	NRVU	VSD	73	0,889	1,58	773	1,48	300	257	68,5	1,3	1,8	E	control panel (HMI)	56,9
HR953-320U EBE75-XE1	2018	NRVU	VSD	73	0,889	1,58	773	1,48	300	257	68,5	1,3	1,8	E	control panel (HMI)	56,9
HR953-320U EBE75-XV1	2018	NRVU	VSD	73	0,889	1,58	773	1,48	300	257	68,5	1,3	1,8	E	control panel (HMI)	56,9
HR953-320U EBE75-XVC	2018	NRVU	VSD	73	0,889	1,58	773	1,48	300	257	68,5	1,3	1,8	E	control panel (HMI)	56,9
HR953-320U EBE75-XD3	2018	NRVU	VSD	73	0,889	1,58	773	1,48	300	257	68,5	1,3	1,8	E	control panel (HMI)	56,9
HR953-320U EBE75-ES0	2018	NRVU	VSD	73	0,889	1,58	773	1,48	300	257	68,5	1,3	1,8	E	control panel (HMI)	56,9
HR953-320U EBE75-EE1	2018	NRVU	VSD	73	0,889	1,58	773	1,48	300	257	68,5	1,3	1,8	E	control panel (HMI)	56,9
HR953-320U EBE75-EV1	2018	NRVU	VSD	73	0,889	1,58	773	1,48	300	257	68,5	1,3	1,8	E	control panel (HMI)	56,9
HR953-320U EBE75-EVC	2018	NRVU	VSD	73	0,889	1,58	773	1,48	300	257	68,5	1,3	1,8	E	control panel (HMI)	56,9
HR953-320U EBE75-ED3	2018	NRVU	VSD	73	0,889	1,58	773	1,48	300	257	68,5	1,3	1,8	E	control panel (HMI)	56,9
HR953-470U EBE75-XS0	2018	NRVU	VSD	77	1,306	2,37	756	1,43	320	252	68,5	0,9	2,3	E	control panel (HMI)	60,4
HR953-470U EBE75-XE1	2018	NRVU	VSD	77	1,306	2,37	756	1,43	320	252	68,5	0,9	2,3	E	control panel (HMI)	60,4
HR953-470U EBE75-XV1	2018	NRVU	VSD	77	1,306	2,37	756	1,43	320	252	68,5	0,9	2,3	E	control panel (HMI)	60,4
HR953-470U EBE75-XVC	2018	NRVU	VSD	77	1,306	2,37	756	1,43	320	252	68,5	0,9	2,3	E	control panel (HMI)	60,4
HR953-470U EBE75-XD3	2018	NRVU	VSD	77	1,306	2,37	756	1,43	320	252	68,5	0,9	2,3	E	control panel (HMI)	60,4
HR953-470U EBE75-ES0	2018	NRVU	VSD	77	1,306	2,37	756	1,43	320	252	68,5	0,9	2,3	E	control panel (HMI)	60,4
HR953-470U EBE75-EE1	2018	NRVU	VSD	77	1,306	2,37	756	1,43	320	252	68,5	0,9	2,3	E	control panel (HMI)	60,4
HR953-470U EBE75-EV1	2018	NRVU	VSD	77	1,306	2,37	756	1,43	320	252	68,5	0,9	2,3	E	control panel (HMI)	60,4
HR953-470U EBE75-EVC	2018	NRVU	VSD	77	1,306	2,37	756	1,43	320	252	68,5	0,9	2,3	E	control panel (HMI)	60,4
HR953-470U EBE75-ED3	2018	NRVU	VSD	77	1,306	2,37	756	1,43	320	252	68,5	0,9	2,3	E	control panel (HMI)	60,4
s) internet address	https://www.2vv.cz/en/products/															

a) suppliers name or trade mark	2VV s.r.o.															
b)		c)	d)	f)	g)	h)	i)	j)	k)	l)	n)	o)		p)	q)	r)
supplier's model identifier	ErP - Conformity (2016/2018/2020)	ErP - Typology (RVU or NRVU)	ErP - Multi-speed drive or variable speed drive	ErP - Thermal efficiency (%)	ErP - nominal air flow (m3/s)	ErP - Effective electric power (kW)	ErP - SFPint (W/(m3/s))	ErP - face velocity at the nominal airflow (m/s)	ErP - nominal external pressure (Pa)	ErP - Internal pressure drop of the components (Pa)	ErP -Static efficiency of fans (%)	ErP - maximum external leakage (%)	ErP - maximum internal leakage (%)	ErP - Energy classification of the filters	ErP - Description of the visual filter warning for the NRVU with filters	ErP - Casing sound power level (LwA(dB))
HR953-150V CBE75-XS0	2018	NRVU	VSD	83,3	0,417	0,89	949	1,38	250	249	56,9	1	1,5	E	control panel (HMI)	57,6
HR953-150V CBE75-XE1	2018	NRVU	VSD	83,3	0,417	0,89	949	1,38	250	249	56,9	1	1,5	E	control panel (HMI)	57,6
HR953-150V CBE75-XV1	2018	NRVU	VSD	83,3	0,417	0,89	949	1,38	250	249	56,9	1	1,5	E	control panel (HMI)	57,6
HR953-150V CBE75-XVC	2018	NRVU	VSD	83,3	0,417	0,89	949	1,38	250	249	56,9	1	1,5	E	control panel (HMI)	57,6
HR953-150V CBE75-XD4	2018	NRVU	VSD	83,3	0,417	0,89	949	1,38	250	249	56,9	1	1,5	E	control panel (HMI)	57,6
HR953-150V CBE75-ES0	2018	NRVU	VSD	83,3	0,417	0,89	949	1,38	250	249	56,9	1	1,5	E	control panel (HMI)	57,6
HR953-150V CBE75-EE1	2018	NRVU	VSD	83,3	0,417	0,89	949	1,38	250	249	56,9	1	1,5	E	control panel (HMI)	57,6
HR953-150V CBE75-EV1	2018	NRVU	VSD	83,3	0,417	0,89	949	1,38	250	249	56,9	1	1,5	E	control panel (HMI)	57,6
HR953-150V CBE75-EVC	2018	NRVU	VSD	83,3	0,417	0,89	949	1,38	250	249	56,9	1	1,5	E	control panel (HMI)	57,6
HR953-150V CBE75-ED4	2018	NRVU	VSD	83,3	0,417	0,89	949	1,38	250	249	56,9	1	1,5	E	control panel (HMI)	57,6
HR953-220V CBE75-XS0	2018	NRVU	VSD	83,9	0,611	1,06	707	1,35	270	212	66,2	0,9	0,8	E	control panel (HMI)	53,4
HR953-220V CBE75-XE1	2018	NRVU	VSD	83,9	0,611	1,06	707	1,35	270	212	66,2	0,9	0,8	E	control panel (HMI)	53,4
HR953-220V CBE75-XV1	2018	NRVU	VSD	83,9	0,611	1,06	707	1,35	270	212	66,2	0,9	0,8	E	control panel (HMI)	53,4
HR953-220V CBE75-XVC	2018	NRVU	VSD	83,9	0,611	1,06	707	1,35	270	212	66,2	0,9	0,8	E	control panel (HMI)	53,4
HR953-220V CBE75-XD4	2018	NRVU	VSD	83,9	0,611	1,06	707	1,35	270	212	66,2	0,9	0,8	E	control panel (HMI)	53,4
HR953-220V CBE75-ES0	2018	NRVU	VSD	83,9	0,611	1,06	707	1,35	270	212	66,2	0,9	0,8	E	control panel (HMI)	53,4
HR953-220V CBE75-EE1	2018	NRVU	VSD	83,9	0,611	1,06	707	1,35	270	212	66,2	0,9	0,8	E	control panel (HMI)	53,4
HR953-220V CBE75-EV1	2018	NRVU	VSD	83,9	0,611	1,06	707	1,35	270	212	66,2	0,9	0,8	E	control panel (HMI)	53,4
HR953-220V CBE75-EVC	2018	NRVU	VSD	83,9	0,611	1,06	707	1,35	270	212	66,2	0,9	0,8	E	control panel (HMI)	53,4
HR953-220V CBE75-ED4	2018	NRVU	VSD	83,9	0,611	1,06	707	1,35	270	212	66,2	0,9	0,8	E	control panel (HMI)	53,4
s) internet address	https://www.2vv.cz/en/products/															

a) suppliers name or trade mark		2VV s.r.o.														
b)		c)	d)	f)	g)	h)	i)	j)	k)	l)	n)	o)		p)	q)	r)
supplier's model identifier	ErP - Conformity (2016/2018/2020)	ErP - Typology (RVU or NRVU)	ErP - Multi-speed drive or variable speed drive	ErP - Thermal efficiency (%)	ErP - nominal air flow (m3/s)	ErP - Effective electric power (kW)	ErP - SFPint (W/(m3/s))	ErP - face velocity at the nominal airflow (m/s)	ErP - nominal external pressure (Pa)	ErP - Internal pressure drop of the components (Pa)	ErP - Static efficiency of fans (%)	ErP - maximum external leakage (%)	ErP - maximum internal leakage (%)	ErP - Energy classification of the filters	ErP - Description of the visual filter warning for the NRVU with filters	ErP - Casing sound power level (LwA(dB))
HR953-320V CBE75-XS0	2018	NRVU	VSD	81,4	0,889	1,44	621	1,48	300	212	68,5	0,8	0,8	E	control panel (HMI)	60,6
HR953-320V CBE75-XE1	2018	NRVU	VSD	81,4	0,889	1,44	621	1,48	300	212	68,5	0,8	0,8	E	control panel (HMI)	60,6
HR953-320V CBE75-XV1	2018	NRVU	VSD	81,4	0,889	1,44	621	1,48	300	212	68,5	0,8	0,8	E	control panel (HMI)	60,6
HR953-320V CBE75-XVC	2018	NRVU	VSD	81,4	0,889	1,44	621	1,48	300	212	68,5	0,8	0,8	E	control panel (HMI)	60,6
HR953-320V CBE75-XD4	2018	NRVU	VSD	81,4	0,889	1,44	621	1,48	300	212	68,5	0,8	0,8	E	control panel (HMI)	60,6
HR953-320V CBE75-ES0	2018	NRVU	VSD	81,4	0,889	1,44	621	1,48	300	212	68,5	0,8	0,8	E	control panel (HMI)	60,6
HR953-320V CBE75-EE1	2018	NRVU	VSD	81,4	0,889	1,44	621	1,48	300	212	68,5	0,8	0,8	E	control panel (HMI)	60,6
HR953-320V CBE75-EV1	2018	NRVU	VSD	81,4	0,889	1,44	621	1,48	300	212	68,5	0,8	0,8	E	control panel (HMI)	60,6
HR953-320V CBE75-EVC	2018	NRVU	VSD	81,4	0,889	1,44	621	1,48	300	212	68,5	0,8	0,8	E	control panel (HMI)	60,6
HR953-320V CBE75-ED4	2018	NRVU	VSD	81,4	0,889	1,44	621	1,48	300	212	68,5	0,8	0,8	E	control panel (HMI)	60,6
HR953-470V CBE75-XS0	2018	NRVU	VSD	82,5	1,306	2,52	871	1,43	320	297	68,5	0,5	0,7	E	control panel (HMI)	62,1
HR953-470V CBE75-XE1	2018	NRVU	VSD	82,5	1,306	2,52	871	1,43	320	297	68,5	0,5	0,7	E	control panel (HMI)	62,1
HR953-470V CBE75-XV1	2018	NRVU	VSD	82,5	1,306	2,52	871	1,43	320	297	68,5	0,5	0,7	E	control panel (HMI)	62,1
HR953-470V CBE75-XVC	2018	NRVU	VSD	82,5	1,306	2,52	871	1,43	320	297	68,5	0,5	0,7	E	control panel (HMI)	62,1
HR953-470V CBE75-XD4	2018	NRVU	VSD	82,5	1,306	2,52	871	1,43	320	297	68,5	0,5	0,7	E	control panel (HMI)	62,1
HR953-470V CBE75-ES0	2018	NRVU	VSD	82,5	1,306	2,52	871	1,43	320	297	68,5	0,5	0,7	E	control panel (HMI)	62,1
HR953-470V CBE75-EE1	2018	NRVU	VSD	82,5	1,306	2,52	871	1,43	320	297	68,5	0,5	0,7	E	control panel (HMI)	62,1
HR953-470V CBE75-EV1	2018	NRVU	VSD	82,5	1,306	2,52	871	1,43	320	297	68,5	0,5	0,7	E	control panel (HMI)	62,1
HR953-470V CBE75-EVC	2018	NRVU	VSD	82,5	1,306	2,52	871	1,43	320	297	68,5	0,5	0,7	E	control panel (HMI)	62,1
HR953-470V CBE75-ED4	2018	NRVU	VSD	82,5	1,306	2,52	871	1,43	320	297	68,5	0,5	0,7	E	control panel (HMI)	62,1
s) internet address	https://www.2vv.cz/en/products/															

a) suppliers name or trade mark		2VV s.r.o.														
b)		c)	d)	f)	g)	h)	i)	j)	k)	l)	n)	o)		p)	q)	r)
supplier's model identifier	ErP - Conformity (2016/2018/2020)	ErP - Typology (RVU or NRVU)	ErP - Multi-speed drive or variable speed drive	ErP - Thermal efficiency (%)	ErP - nominal air flow (m3/s)	ErP - Effective electric power (kW)	ErP - SFPint (W/(m3/s))	ErP - face velocity at the nominal airflow (m/s)	ErP - nominal external pressure (Pa)	ErP - Internal pressure drop of the components (Pa)	ErP -Static efficiency of fans (%)	ErP - maximum external leakage (%)	ErP - maximum internal leakage (%)	ErP - Energy classification of the filters	ErP - Description of the visual filter warning for the NRVU with filters	ErP - Casing sound power level (LwA(dB))
HR953-150V EBE75-XS0	2018	NRVU	VSD	74,4	0,417	0,77	647	1,38	250	186	56,9	1	1,5	E	control panel (HMI)	54,7
HR953-150V EBE75-XE1	2018	NRVU	VSD	74,4	0,417	0,77	647	1,38	250	186	56,9	1	1,5	E	control panel (HMI)	54,7
HR953-150V EBE75-XV1	2018	NRVU	VSD	74,4	0,417	0,77	647	1,38	250	186	56,9	1	1,5	E	control panel (HMI)	54,7
HR953-150V EBE75-XVC	2018	NRVU	VSD	74,4	0,417	0,77	647	1,38	250	186	56,9	1	1,5	E	control panel (HMI)	54,7
HR953-150V EBE75-XD4	2018	NRVU	VSD	74,4	0,417	0,77	647	1,38	250	186	56,9	1	1,5	E	control panel (HMI)	54,7
HR953-150V EBE75-ES0	2018	NRVU	VSD	74,4	0,417	0,77	647	1,38	250	186	56,9	1	1,5	E	control panel (HMI)	54,7
HR953-150V EBE75-EE1	2018	NRVU	VSD	74,4	0,417	0,77	647	1,38	250	186	56,9	1	1,5	E	control panel (HMI)	54,7
HR953-150V EBE75-EV1	2018	NRVU	VSD	74,4	0,417	0,77	647	1,38	250	186	56,9	1	1,5	E	control panel (HMI)	54,7
HR953-150V EBE75-EVC	2018	NRVU	VSD	74,4	0,417	0,77	647	1,38	250	186	56,9	1	1,5	E	control panel (HMI)	54,7
HR953-150V EBE75-ED4	2018	NRVU	VSD	74,4	0,417	0,77	647	1,38	250	186	56,9	1	1,5	E	control panel (HMI)	54,7
HR953-220V EBE75-XS0	2018	NRVU	VSD	79,1	0,611	1,00	600	1,35	270	183	66,2	0,9	0,8	E	control panel (HMI)	52,3
HR953-220V EBE75-XE1	2018	NRVU	VSD	79,1	0,611	1,00	600	1,35	270	183	66,2	0,9	0,8	E	control panel (HMI)	52,3
HR953-220V EBE75-XV1	2018	NRVU	VSD	79,1	0,611	1,00	600	1,35	270	183	66,2	0,9	0,8	E	control panel (HMI)	52,3
HR953-220V EBE75-XVC	2018	NRVU	VSD	79,1	0,611	1,00	600	1,35	270	183	66,2	0,9	0,8	E	control panel (HMI)	52,3
HR953-220V EBE75-XD4	2018	NRVU	VSD	79,1	0,611	1,00	600	1,35	270	183	66,2	0,9	0,8	E	control panel (HMI)	52,3
HR953-220V EBE75-ES0	2018	NRVU	VSD	79,1	0,611	1,00	600	1,35	270	183	66,2	0,9	0,8	E	control panel (HMI)	52,3
HR953-220V EBE75-EE1	2018	NRVU	VSD	79,1	0,611	1,00	600	1,35	270	183	66,2	0,9	0,8	E	control panel (HMI)	52,3
HR953-220V EBE75-EV1	2018	NRVU	VSD	79,1	0,611	1,00	600	1,35	270	183	66,2	0,9	0,8	E	control panel (HMI)	52,3
HR953-220V EBE75-EVC	2018	NRVU	VSD	79,1	0,611	1,00	600	1,35	270	183	66,2	0,9	0,8	E	control panel (HMI)	52,3
HR953-220V EBE75-ED4	2018	NRVU	VSD	79,1	0,611	1,00	600	1,35	270	183	66,2	0,9	0,8	E	control panel (HMI)	52,3
s) internet address	https://www.2vv.cz/en/products/															

a) suppliers name or trade mark		2VV s.r.o.														
b)		c)	d)	f)	g)	h)	i)	j)	k)	l)	n)	o)		p)	q)	r)
supplier's model identifier	ErP - Conformity (2016/2018/2020)	ErP - Typology (RVU or NRVU)	ErP - Multi-speed drive or variable speed drive	ErP - Thermal efficiency (%)	ErP - nominal air flow (m3/s)	ErP - Effective electric power (kW)	ErP - SFPint (W/(m3/s))	ErP - face velocity at the nominal airflow (m/s)	ErP - nominal external pressure (Pa)	ErP - Internal pressure drop of the components (Pa)	ErP -Static efficiency of fans (%)	ErP - maximum external leakage (%)	ErP - maximum internal leakage (%)	ErP - Energy classification of the filters	ErP - Description of the visual filter warning for the NRVU with filters	ErP - Casing sound power level (LwA(dB))
HR953-320V EBE75-XS0	2018	NRVU	VSD	73	0,889	1,50	693	1,48	300	234	68,5	0,8	0,8	E	control panel (HMI)	61,2
HR953-320V EBE75-XE1	2018	NRVU	VSD	73	0,889	1,50	693	1,48	300	234	68,5	0,8	0,8	E	control panel (HMI)	61,2
HR953-320V EBE75-XV1	2018	NRVU	VSD	73	0,889	1,50	693	1,48	300	234	68,5	0,8	0,8	E	control panel (HMI)	61,2
HR953-320V EBE75-XVC	2018	NRVU	VSD	73	0,889	1,50	693	1,48	300	234	68,5	0,8	0,8	E	control panel (HMI)	61,2
HR953-320V EBE75-XD4	2018	NRVU	VSD	73	0,889	1,50	693	1,48	300	234	68,5	0,8	0,8	E	control panel (HMI)	61,2
HR953-320V EBE75-ES0	2018	NRVU	VSD	73	0,889	1,50	693	1,48	300	234	68,5	0,8	0,8	E	control panel (HMI)	61,2
HR953-320V EBE75-EE1	2018	NRVU	VSD	73	0,889	1,50	693	1,48	300	234	68,5	0,8	0,8	E	control panel (HMI)	61,2
HR953-320V EBE75-EV1	2018	NRVU	VSD	73	0,889	1,50	693	1,48	300	234	68,5	0,8	0,8	E	control panel (HMI)	61,2
HR953-320V EBE75-EVC	2018	NRVU	VSD	73	0,889	1,50	693	1,48	300	234	68,5	0,8	0,8	E	control panel (HMI)	61,2
HR953-320V EBE75-ED4	2018	NRVU	VSD	73	0,889	1,50	693	1,48	300	234	68,5	0,8	0,8	E	control panel (HMI)	61,2
HR953-470V EBE75-XS0	2018	NRVU	VSD	77	1,306	2,34	731	1,43	320	253	68,5	0,5	0,7	E	control panel (HMI)	60,5
HR953-470V EBE75-XE1	2018	NRVU	VSD	77	1,306	2,34	731	1,43	320	253	68,5	0,5	0,7	E	control panel (HMI)	60,5
HR953-470V EBE75-XV1	2018	NRVU	VSD	77	1,306	2,34	731	1,43	320	253	68,5	0,5	0,7	E	control panel (HMI)	60,5
HR953-470V EBE75-XVC	2018	NRVU	VSD	77	1,306	2,34	731	1,43	320	253	68,5	0,5	0,7	E	control panel (HMI)	60,5
HR953-470V EBE75-XD4	2018	NRVU	VSD	77	1,306	2,34	731	1,43	320	253	68,5	0,5	0,7	E	control panel (HMI)	60,5
HR953-470V EBE75-ES0	2018	NRVU	VSD	77	1,306	2,34	731	1,43	320	253	68,5	0,5	0,7	E	control panel (HMI)	60,5
HR953-470V EBE75-EE1	2018	NRVU	VSD	77	1,306	2,34	731	1,43	320	253	68,5	0,5	0,7	E	control panel (HMI)	60,5
HR953-470V EBE75-EV1	2018	NRVU	VSD	77	1,306	2,34	731	1,43	320	253	68,5	0,5	0,7	E	control panel (HMI)	60,5
HR953-470V EBE75-EVC	2018	NRVU	VSD	77	1,306	2,34	731	1,43	320	253	68,5	0,5	0,7	E	control panel (HMI)	60,5
HR953-470V EBE75-ED4	2018	NRVU	VSD	77	1,306	2,34	731	1,43	320	253	68,5	0,5	0,7	E	control panel (HMI)	60,5
s) internet address	https://www.2vv.cz/en/products/															